

# AVI201

## Network Camera

(cost-effective)



### ● FEATURES

- (1) Low-latency video streaming for sharp and clear images
- (2) Hybrid digital / analog video output
- (3) Motion detection and alarm notification functions
- (4) High quality image sensor
- (5) Complete IP surveillance system, such as the Central Management System (CMS) software, Network-Attached Storage (NAS), Network Video Recorder (NVR), etc.

### ● SPECIFICATION

AVI201	
<b>■ Network</b>	
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
Frame Rate	NTSC:30, PAL:25
Number of Online Users	10
Security	Multiple user access levels with password
Web management software	YES (Control up to 16 network cameras simultaneously)
<b>■ Video</b>	
Video Compression	MPEG4 / MJPEG
Video Remote Control	YES
Video Adjustment	Brightness, Contrast, Saturation and Hue

● **SPECIFICATION (CONTINUED...)**

<b>AVI201</b>	
<b>■ Camera</b>	
Image Sensor	1/3.6" image sensor
Pixels	738(H) x 480(V)
Resolutions	480TV lines
Lens	f3.6
F-number	F2.0
Viewing Angle	80°
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.
Min Illumination	1 Lux / F2.0
Video Output	1.0 Vp-p. 75Ω
BLC	AUTO
White Balance	ATW
<b>■ Others</b>	
Remote Control	YES
Motion Detection	YES
Alarm and event Notification	Image upload over FTP and E-mail
General I/O	NO
Power	12VDC, 0.2A
Operating Temperature	0~40°C
Humidity	85%
Minimum Web Browsing Requirements	<ul style="list-style-type: none"> <li>• Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD</li> <li>• 256 MB RAM</li> <li>• AGP graphics card , Direct Draw, 32MB RAM</li> <li>• Windows XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later</li> <li>• Internet Exploerer 6.x or later</li> </ul>
Dimension (mm)**	158 x 40.2 x 115.2
In/Out Door Use	Indoor

\* The specifications are subject to change without notice.

\*\* Dimensional tolerance: (± 5mm)